

AUTOMATIC PARKING SPACE PROTECTOR

UNIPARK PRO

MODEL UPL-600

Secure reserved parking spaces at the touch of a button. A compact, battery-powered solution engineered for dependable outdoor use.



HEAVY-DUTY STEEL

2000 KG

LOAD CAPACITY

IP67

PROTECTION

600 MM

RISING HEIGHT

-40~+70°C

OPERATING RANGE

Built for dependable daily protection

A practical parking-space control solution with premium outdoor engineering.



UPL-600

Own the space. Control the access.

UniPark Pro rises to reserve a parking bay and folds down to only 75 mm for easy vehicle access. Remote operation eliminates the need for fixed cabling.

Core advantages



Remote operation

Convenient raise and lower control from the vehicle.



Steel construction

Durable frame designed for frequent parking use.



Low folded profile

Only 75 mm high when lowered for smooth vehicle passage.



IP67 protection

Sealed outdoor design resists dust and water ingress.



Battery powered

Stand-alone installation with no permanent power cable.



2000 kg capacity

Robust structural load rating for demanding environments.

IDEAL FOR Villas | Offices | Residential buildings | Reserved bays | Commercial parking

Simple operation

01

Press remote

02

Lock rises

03

Space protected

Technical performance, clearly defined

Dimensions and operating parameters for AGMATIC UniPark Pro UPL-600.

KEY DIMENSIONS



75 mm

FOLDED HEIGHT



8 kg

NET WEIGHT



DC 6V

RATED VOLTAGE

Technical specifications

Product	Automatic parking lock
Model	AGMATIC UPL-600
Dimensions - folded	470 x 400 x 80 mm
Material	Steel
Rising height	600 mm
Falling / folded height	75 mm
Weight	8 kg
Loading capacity	2000 kg
Control mode	Remote-control operation
Protection level	IP67
Power supply	Battery
Rated voltage	DC 6V
Operating temperature	-40°C to +70°C
Warranty	12 months

ENGINEERED FOR OUTDOOR USE

IP67

A sealed protection level suitable for exposed parking locations, combined with a broad operating temperature range.

DUST

Protected against ingress

WATER

Outdoor-ready enclosure

TEMPERATURE

-40°C to +70°C

Configure your UniPark Pro

Standard supply, extended power choices, and smart-control options.

Standard accessories

Included with the standard product



3x expanding bolts

Secure floor fixing



2x manual keys

Emergency access



2x remote controls

Wireless operation



Standard battery set

Ready for installation

Optional battery packages



D-size dry battery

4-5 months

Standard replacement



Rechargeable lead-acid

6-7 months

Per full charge



Rechargeable lithium

8-9 months

Per full charge

* Battery endurance is indicative and varies with operating frequency, temperature, and site conditions.

Advanced control options



Solar energy



App control



Smart sensing



Group control

AGMATIC

Ajman Free Zone, Ajman

www.agmatic.ae | Email: info@agmatic.ae | Tel: +971 6 5959 344

Specifications may be updated without prior notice. Images are for product presentation.